



AI.LXT201




TECHNICAL DATA

- **Enclosure housing:** Explosion proof - EEx d IIC-T6, II 2 GD; IP66
- **Process connection:** 1 1/2" - 3" NPT(M), thread type
- **Material:** Wetted parts 316 stainless steel
- **Maximum Temperature:** -20°C to +150°C
- **Pressure Limits:** 3.0 Mpa (30 kg/cm²), option: up to 4.5 Mpa
- **Switch function:** Micro switch 1 x SPDT; 2 x SPDT option
- **Switch rating:** 3A/250VAC, 5A/125VAC, 4A/30VDC
- **Conduit connection:** 1/2" NPT (F), 3/4" NPT (F), option available
- **Float working specific gravity:** ≥ 0.7 (option: less than 0.7 available on request)

DIMENSION



WIRE DRAWING



1 SPDT



2 SPDT

ORDERING INFORMATION

LXT201	Code	Type
	S	Standard type
	E	Extension Arm Type
	Code	Process Connection Size
		(1) 1 1/2" (2) 2" (3) 3" (4) Option
	Code	Process Connection Rating - Male
		(A) NPT (B) Option
	Code	Conduit Connection Size
		(1) 1/2"NPT (2) 3/4"NPT (3) Option
	Code	Wetted Parts Material
		(1) SS316 (2) Option
	Code	Switch Function- Micro Switch
	1	One switch, SPDT x 1
	2	Two switch, SPDT x 2
LXT201		Complete Ordering Code



ASIT ITALIA S.R.L.

Sede operativa e Uffici
Via Quintino Sella, 6
10020 Riva presso Chieri (TO)
T (+39) 011 198 218 39 - F (+39) 011 198 371 06

INFO@ASIT-GE.COM

WWW.ASIT-GE.COM



Company with
Certificate of Quality
System ISO 9001:2015
Cert n°38785/19/S